
























PALIO LOOSELAY Technical specification

Palio
LooseLay

PALIO LOOSELAY

	STANDARD	RESULT
	SIZE	EN ISO 24342 Plank: 1050 x 250mm (41.3"x9.85") Tile: 500 x 610mm (19.7" x 24")
	THICKNESS	EN ISO 24346 4.5mm
	WEAR LAYER	EN ISO 24340 0.55mm
	SURFACE TREATMENT	PU coating
	GUARANTEE	Light industrial Commercial Domestic 15 years* 15 years* Lifetime guarantee*
	BEVELLED EDGE	No
	MASS	EN ISO 23997 7550 g/m ²
	STANDARDS	EN 649/EN ISO 10582 Pass
	CLASSIFICATION	EN 685/EN ISO 10874- Light industrial EN 685/EN ISO 10874- Commercial EN 685/EN ISO 10874- Domestic 42: Light industrial general 33: Commercial heavy 23: Domestic heavy
	REACTION TO FIRE	EN 13501-1 B _{f1} -s1
	STAINING RESISTANCE	EN 423 Class 0
	LIGHT FASTNESS	EN ISO 105-B02 7
	ABRASION RESISTANCE	EN 649 EN ISO 10582 Group T Type 1
	FLEXIBILITY	EN ISO 24344 Pass
	DIMENSIONAL STABILITY	EN 434/EN ISO 23999 ≤ 0.10%
	ACOUSTIC IMPACT NOISE REDUCTION	EN ISO 717-2 / EN ISO 140-8 ΔL _W = 13 dB
	ELECTRICAL BEHAVIOUR BODY VOLTAGE	EN 1815 Pass
	INDENTATION - RESIDUAL	EN 433/EN ISO 24343-1 Pass ≤ 0.1mm
	CASTOR CHAIR CONTINUOUS USE	EN 425/ISO 4918 Pass
	THERMAL RESISTANCE	ISO 8302 0.0245 m ² K/W Suitable for underfloor heating. Max 27°C
	SLIP RESISTANCE**	BS 7976 DIN 51130 DIN 51097 EN 13893 Plank: Dry: 61 Wet: 33 Tile: Dry: 66 Wet: 29 R10 Plank: B Tile: A DS
	LIGHT REFLECTANCE VALUE (LRV)	BS 8493:2008+A1:2010 See separate table
	VOC EMISSION	French VOC regulation (ISO 16000) A+
	ADHESIVE	None required; please install according to our installation instructions.
	RECYCLING	Suitable

PRODUCT	LRV
LLPI42	26
LLPI43	20
LLPI44	34
LLPI45	27
LLPI46	27
LLPI47	38
LLPI48	21
LLPI49	46
LLPI50	25
LLPI51	9
LLT208	66
LLT209	44
LLT210	23
LLT211	10

*Subject to terms. Please see our website.

**Slip resistance is measured on ex-factory product. Slip resistance in use will be affected by surface contamination, use and how the product is maintained.



Manufactured to ISO 9001