


## Contour ShowerDec Wet Room Tray Floor Former - 1800 x 900mm



Contour ShowerDec Wet Room Tray Floor Former



Contour ShowerDec 1800 x 900 x 24mm



Rating: Not Rated Yet

**Price**

Base price with tax £558.00

Sales price £345.96

Discount £-212.04

Tax amount £57.66

[Ask a question about this product](#)

Manufacturer [Contour Showers](#)

Description

## SPECIFICATION

- **1800 x 900 x 24mm**
- **UNDER-SUPPORT NOT REQUIRED**
- **TILED OR VINYL DRAIN OPTIONS**
- **SUPPORTS UP TO 653KG**
- **CAN BE TRIMMED**
  
- **LIFETIME GUARANTEE\***

## SUITABLE FOR

- **WOOD OR CONCRETE SUBFLOOR**
- **TILED FLOOR FINISH**
- **VINYL FLOOR FINISH**
- **WET ROOMS**
- **LEVEL ACCESS**
- **RAISED ON PLATFORM**
- **USE WITH WHEELCHAIRS**
- **FITTING DIRECT ON JOISTS**
- **UNDERFLOOR HEATING**

## NOT SUITABLE FOR

- **MICRO-CEMENT**

The ShowerDec from Contour is an incredibly strong wet room / walk in shower former tray that is suitable for tiled or vinyl floor finish, and can be installed in wooden or concrete sub floors. Designed for level access wet rooms and shower areas, the ShowerDec is suitable for use with wheelchairs and similar devices, with out the need for under supporting.

The ShowerDec is tested to withstand **100 stone / 635Kg** across the entire surface area to simulate a standing person. At just **24mm thick** the ShowerDec is suitable for installing direct onto floor joists, the remaining floor should then be boarded to the same level.

ShowerDec floor formers are available in 11 size options and can be further cut to size using a circular saw or jigsaw. The ShowerDec features offset drain positions designed to avoid joists, trays are not handed. A standard vinyl waste and stainless steel tile and vinyl waste options are available.

#### Installer Friendly:

- No raised collar around the underside of the waste making installation on timber floors easier.
- No additional support is needed around the waste assisting ease & speed of installation.\*
- 40mm flat area around the floor former perimeter for door placement & water retention.
- Larger shower area, ideal for wheelchairs.
- Circular ribbed underside designed for setting into a concrete or screed base and eliminates slippage when installing.
- Textured top surface allows excellent adhesion of vinyl flooring.
- Offset waste positions to avoid joists.
- Excellent falls of approximately **2% - 2.5%** built into the top surface - 'BEST IN CLASS'.
- Pre-formed semi-drilled fixing points for secure installation.
- Can be cut to size in virtually any position using a circular saw or jigsaw.
- Suitable for timber & screeded floors

*\*Tested in accordance with a standard floor with 16" joist centres of 47mm width & supported around the floor former outer edges.*

#### Waste Options:

**CTW01** - 2 part, 50mm water sealed, flow rate in excess of **26 l/m**. White cover plate suitable for vinyl only.

**TSG52** - 2 part, 50mm water sealed, flow rate in excess of **40 l/m**. Stainless steel grate for vinyl (round) or tiled (square) floor (please specify).

Other drain options on request.

#### Optional Tanking for Tiled Floor Finish:

If installing the ShowerDec with a tiled floor the tray and joints to the surround of the tray will need to be tanked (waterproofed) prior to the laying of tiles. Two tanking options exist for this:

#### Jackoboard Paint-On Tanking Kit:



The Jackoboard tanking kit contains a rapid drying, brush/roller applied, single part flexible liquid membrane for use on rigid surfaces in bathrooms, wetrooms and showers. It can also be used to waterproof existing surfaces such as plaster, plasterboard or timber.

Suitable for all flat or vertical surfaces made of any material. Simple to use for novices and experts alike. Compatible with almost every type of under floor heating and ready for tiling with no further preparation (please check with under floor heating manufacturer).

For use under ceramic coverings in wet rooms, showers and bathrooms. Coverage 5 - 6sqm under normal conditions with recommended two coats.

Jackoboard Paint-On tanking kit contents:

- 4kg (2.5 litre) Tanking solution
- 1 litre primer for timber/plasterboard
- 10m sealing tape
- 2 x internal corners seals

### Contour Tanking Membrane Kit:



- A pre-formed flexible self-adhesive waterproof membrane.
- Permanent waterproof bond for use prior to laying tiles onto a wetroom floor.
- Ideal for use on timber, masonry, concrete, plasterboards, gypsum & existing ceramic or natural stone.
- Once applied, the membrane is ready to tile immediately.
- Membrane is cold applied, consisting of a 1mm thick butyl waterproof layer, incorporating a fleece on one side.
- Can be installed over a thermal board.
- Suitable for use with underfloor heating - Heating should be restricted at **32°**. **Electrical heating max 150w**.
- Guaranteed for the lifetime of the tiled area when installed as per the manufacturers recommendations.
- Available in 5m<sup>2</sup> or 10m<sup>2</sup> kits.

Contour Membrane tanking kit contents:

5m<sup>2</sup> or 10m<sup>2</sup> Membrane,  
500ml Primer,  
10m Reinforcing Tape,  
1 x Jointing Compound,  
4 x Pre-formed Internal Corners.

### Downloads:

[Contour Shower Dec Installation Instructions](#)

[Contour Shower Dec Product Sheet](#)

[Contour Tanking Membrane Instructions](#)